

DFL D 255 (924 395)


Acoustic fault indication

Compact design


For use in flush-mounted systems, cable ducts and flush-type boxes



Figure without obligation



Basic circuit diagram DFL D 255



Dimension drawing DFL D 255

Surge arrester for use in all types of installation systems for terminal equipment; allows for through-wiring; with test function

Type	DFL D 255
Part No.	924 395
SPD according to EN 61643-11	Type 3
SPD according to IEC 61643-1	Class III
Nominal a.c. voltage (U_N)	230 V
Max. continuous operating a.c. voltage (U_C)	255 V
Nominal load current a.c. (I_L)	16 A
Nominal discharge current (8/20 μ s) (I_n)	3 kA
Total discharge current (8/20 μ s) [L+N-PE] (I_{total})	5 kA
Combined impulse (U_{OC})	6 kV
Combined impulse [L+N-PE] ($U_{OC total}$)	10 kV
Voltage protection level [L-N] (U_P)	≤ 1.25 kV
Voltage protection level [L/N-PE] (U_P)	≤ 1.5 kV
Response time [L-N] (t_A)	≤ 25 ns
Response time [L/N-PE] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	16 A gL/gG or B 16 A
Short-circuit withstand capability for mains-side overcurrent protection with 16 A gL/gG	6 kA _{rms}
Temporary overvoltage (TOV) [L-N] (U_T)	335 V / 5 sec.
Temporary overvoltage (TOV) [L/N-PE] (U_T)	400 V / 5 sec.
Temporary overvoltage (TOV) [L+N-PE] (U_T)	1200 V + U_{CS} / 200 ms
TOV characteristic [L-N]	withstand
TOV characteristic [L/N-PE]	withstand
TOV characteristic [L+N-PE]	safe
Fault indication	acoustic signal on
Number of ports	1
Operating temperature range (T_U)	-25°C...+40°C
Terminal wires	2.5 mm ² , length: 120 mm
Enclosure material	thermoplastic, red, UL 94 V-2
Place of installation	indoor
Degree of protection of installed device	IP 20
Dimensions	36 x 46 x 19 mm
Weight	66,9 g
Customs tariff number	85363010
GTIN	4013364076334
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.