


# Integral Palms Tinned Copper Earth Braid – 556650



- Higher electrical contact due to integral palms
- Excellent tensile strength
- Good resistance to vibration and fatigue
- Possible to bend very close to the contact area
- Recommended by the EMC directives
- Tinned electrolytic copper 0,15 mm wire
- Area working temperature up to 105°C
- UL467 File E220029



Part Number	556650
Description	MBJ 16-250-8
Approvals	UL®
Conductor Type	Tinned Copper
Cross Section	16 mm <sup>2</sup>
Current	120 A
Hole Diameter	8,5 mm
J	15 mm
L	250 mm
Length	250 mm
Palm Length	25 mm
Standard Packaging Quantity	10
T	25 mm
Thickness	1,5 mm
Weight	0,04 kg
Standard Packaging Quantity	10 pc
UPC	78285644966

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

